



INSTAFLEX Adapter PB/Brass Socket fusion transition to male thread

Socket fusion transition to male thread
Thread in DZR brass, UBA (Umwelt Bundesamt, Germany) conform
Gasket: EPDM, quality for potable water

- Material: PB, Brass
- Approvals: hot- and cold water approved
- Operation pressure: 16 bars
- Brass: low lead content

d (mm)	R (inch)	Code	SP	Weight (kg)	L (mm)	z (mm)	k max. (mm)
16	1/2	761 069 666	1	0.083	96	83	22
20	1/2	761 069 667	1	0.106	99	86	24
20	3/4	761 069 668	1	0.120	101	86	24
25	3/4	761 069 669	1	0.146	104	89	23
25	1	761 069 670	1	0.161	107	90	23
32	1	761 069 671	1	0.239	111	94	21
40	1 1/4	761 069 672	1	0.389	133	114	24
50	1 1/2	761 069 673	1	0.489	138	119	22
63	2	761 069 674	1	0.808	156	132	21

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland

Phone +41 -(0)52-631 1111

e-mail: info.ps@georgfischer.com

Internet: <http://www.gfps.com>