



Type 2260 Level Transmitter, Continuous Measuring, Display Version, 4-20 mA / HART / Relay Output

- Principle: non-contact ultrasonic transit time
- Measuring range: 0.2...4 m, 0.25...6 m, 0.45...15 m
- Sensor Type: PP or PVDF
- Output: 4-20 mA, 2-wire; HART Protocol; Relay
- Integrated display and programming buttons
- Supply power: 12...36 V DC

MFR #	Measuring range (m)	Process Connection	Sensor Type
2260-P-2DB-4	0.20 - 4.00	1 1/2" BSP	PP
2260-P-2DB-6	0.25 - 6.00	2" BSP	PP
2260-P-2DF-15	0.45 - 15.00	DN 125 flange	PP
2260-V-2DB-4	0.20 - 4.00	1 1/2" BSP	PVDF
2260-V-2DB-6	0.25 - 6.00	2" BSP	PVDF
2260-P-2DA-15	0.45 - 15.00	DN 125 flange	PVDF
2260-V-2DN-4	0.20 - 4.00	1 1/2" NPT	PP
2260-V-2DN-6	0.25 - 6.00	2" NPT	PP
2260-P-2DA-15	0.45 - 15.00	ANSI Flange 5 inch	PP
2260-V-2DN-4	0.20 - 4.00	1 1/2" NPT	PVDF
2260-V-2DN-6	0.25 - 6.00	2" NPT	PVDF
2260-P-2DA-15	0.45 - 15.00	ANSI Flange 5 inch	PVDF

Code	Weight (kg)	PF
159 300 091	0.790	3 86 376 005
159 300 093	0.790	3 86 376 005
159 300 095	5.000	3 86 376 005
159 300 102	0.790	3 86 376 005
159 300 104	0.790	3 86 376 005
159 300 106	5.000	3 86 376 005
159 300 121	0.790	3 86 376 005
159 300 123	0.790	3 86 376 005
159 300 125	5.000	3 86 376 005
159 300 132	0.790	3 86 376 005
159 300 134	0.790	3 86 376 005
159 300 136	0.790	3 86 376 005

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland

Phone +41 -(0)52-631 1111

e-mail: info.ps@georgfischer.com

Internet: <http://www.gfps.com>