



SYGEF Plus union (FKM white) SDR21/PN16
Gap filling O-ring positioning
High Purity clean-room product ISO Class 5 (1)

Model:

- Material: PVDF-HP
- gap filling O-ring positioning
- FDA compliant
- d75, d90 and d110 with buttress shaped thread
- Please see installation instruction

d (mm)	PN (bar)	SDR	FM	Code	SP	GP	Weight (kg)
20	16	21	BCF, IR	735 528 626	1	30	0.082
25	16	21	BCF, IR	735 528 627	1	20	0.123
32	16	21	BCF, IR	735 528 628	1	15	0.166
40	16	21	BCF, IR	735 528 629	1	20	0.263
50	16	21	BCF, IR	735 528 630	1	6	0.372
63	16	21	BCF, IR	735 528 631	1	12	0.463
75	16	21	BCF, IR	735 528 637	1	8	0.740
90	16	21	BCF, IR	735 528 638	1	8	0.798
110	16	21	BCF, IR	735 528 639	1	5	1.020

d (mm)	G (R/Rp BS Thread) (inch)	e (mm)	D (mm)	L (mm)	L1 (mm)	L2 (mm)	L3 (mm)	L4 (mm)
20	1	1.9	43	106	53	53	25	37
25	1 1/4	1.9	53	112	56	56	25	38
32	1 1/2	2.4	60	118	59	59	25	40
40	2	2.4	74	124	62	62	25	41
50	2 1/4	3.0	82	130	65	65	25	43
63	2 3/4	3.0	100	136	68	68	25	44
75	S 107.5 x 3.6	3.6	133	132	66	66	24	34
90	S 107.5 x 3.6	4.3	133	130	65	65	24	48
110	S 127.5 x 3.6	5.3	155	130	65	65	25	45

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland

Phone +41 -(0)52-631 1111

e-mail: info.ps@georgfischer.com

Internet: <http://www.gfps.com>