




COOL-FIT 2.0 Tee 90° reduced, short

Model:

- Pre-insulated PE100 SDR11, metric
- Insulation made from GF HE foam
- Impact resistant. Color: black
- A: Electrofusion Fitting with integrated sealing lip, for a water and vapour tight sealing
- Space-optimized branch: sealing lip of Fitting Typ A that joins to the branch, needs to be cut and adhesive ring be use



d/D (mm)	DN (mm)	SDR	d1 (mm)	PN (bar)	Code	L (mm)	L1 (mm)	L2 (mm)	z (mm)	z1 (mm)	Closest inch (inch)	Type
40/90	32	11	32	16	738 204 506	81	40	36	22	108	1 ¼ - 1	A
50/90	40	11	32	16	738 204 509	88	44	36	25	117	1 ½ - 1	A
63/110	50	11	32	16	738 204 512	97	48	36	30	135	2 - 1	A
75/125	65	11	32	16	738 204 515	110	55	36	36	121	2 ½ - 1	A
90/140	80	11	32	16	738 204 519	124	62	36	43	135	3 - 1	A
110/160	100	11	32	16	738 204 524	148	72	36	57	148	4 - 1	A

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland

Phone +41 -(0)52-631 1111

e-mail: info.ps@georgfischer.com

Internet: <http://www.gfps.com>