




COOL-FIT 4.0 Elbow 90° d32-d225

Model:

- Pre-insulated PE100 SDR11, metric
- Insulation made from GF HE foam
- Outer jacket impact resistant. Color: black
- A: Electrofusion Fitting with integrated sealing lip, for a water and vapour tight sealing



d/D (mm)	DN (mm)	SDR	PN (bar)	Code	Weight (kg)	D1 (mm)	L (mm)	L1 (mm)	z (mm)	closest inch (inch)	Type
32/90	25	11	16	738 103 108	0.255	97	81	36	20	1	A
40/110	32	11	16	738 103 109	0.177	117	88	40	23	1 ¼	A
50/110	40	11	16	738 103 110	0.250	117	99	44	30	1 ½	A
63/125	50	11	16	738 103 111	0.372	132	107	48	34	2	A
75/140	65	11	16	738 103 112	0.800	147	120	55	40	2 ½	A
90/160	80	11	16	738 103 113	1.500	168	150	62	63	3	A
110/180	90	11	16	738 103 114	1.950	188	174	72	77	4	A
160/250	150	11	16	738 103 117	5.200	258	220	90	105	6	A
225/315	200	11	16	738 103 120	12.400	324	345	110	210	8	A

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland

Phone +41 -(0)52-631 1111

e-mail: info.ps@georgfischer.com

Internet: <http://www.gfps.com>