



## COOL-FIT 4.0 fixed point

### Model:

- The product consists of two components namely electrofusion tapes and pipe brackets.
- Electrofusion welded tape as permanent connection to transmit the forces that occur in the pipe to the fixed point.
- The delivered pipe brackets are needed to deliver welding pressure during installation and give stability during operation.
- For welding, use an MSA2.x, MSA4.x, MSA 250, 300, 350, 400 or commercially available 220 V fusion machines.
- If you use an MSA fusion machine from GF Piping Systems, use the 799 350 339 adapter or the 790 156 032 y-cable set.
- Please take note of the maximum allowed forces for this version in the table below.
- **Fixed point brackets and cross braces have to be calculated and obtained by the installer. They are not included in the fixed point set from GF.**

D (mm)	d (mm)	Code	SP	Weight (kg)	L (mm)	H (mm)	max Force (kN)	Closest inch (inch)
90	32	738 912 013	1	0.895	170	60	2.0	1 ¼ - 1 ½
110	40 - 50	738 912 014	1	0.904	180	60	3.0 / 5.0	2
125	63	738 912 015	1	1.103	215	60	8.0	2 ½
140	75	738 912 016	1	1.188	220	60	10.0	3
160	90	738 912 017	1	1.177	255	60	10.0	4
180	110	738 912 018	1	1.530	255	60	10.0	4
250	160	738 912 021	1	1.957	335	60	10.0	6
315	225	738 912 023	1	2.388	400	60	10.0	8
355	250	738 912 024	1	2.388	420	60	10.0	10

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland

Phone +41 -(0)52-631 1111

e-mail: [info.ps@georgfischer.com](mailto:info.ps@georgfischer.com)

Internet: <http://www.gfps.com>