



## COOL-FIT 2.0F fixed point set

### Model:

- Four PVC-U half shells as permanent connection to transmit the forces that occur in the pipe to the fixed point.
- For cementing use Tangit RAPID, Tangit RAPID static mixer and Tangit RAPID dispenser
- Please take note of the maximum allowed forces for this version in the table below.
- **Fixed point brackets and cross braces have to be calculated and obtained by the installer. They are not included in the fixed point set from GF.**

D (mm)	d (mm)	Code	Weight (kg)	L (mm)	H (mm)	max. Force (kN)	closest inch (inch)
75	32	<b>738 912 312</b>	0.750	87	30	2.0	1
90	40 - 50	<b>738 912 313</b>	0.895	105	35	3.0 / 5.0	1 ¼ / 1 ½
110	63	<b>738 912 314</b>	0.904	128	35	8.0	2
125	75	<b>738 912 315</b>	1.103	142	35	10.0	2 1/2
140	90	<b>738 912 316</b>	1.188	162	35	10.0	3
160	110	<b>738 912 317</b>	1.177	183	35	10.0	4
200	140	<b>738 912 319</b>	1.600	221	35	10.0	5

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland

Phone +41 -(0)52-631 1111

e-mail: [info.ps@georgfischer.com](mailto:info.ps@georgfischer.com)

Internet: <http://www.gfps.com>