



Air release/foot valve B.S.P. PVC-U With threaded sockets Rp

- Standards: UNI ISO 228/1, DIN 2999, BS21
- (*) Body and dimensions = 3"

PN (bar)	DN (mm)	Rp (inch)	EPDM Code	SP	Weight (kg)	Z (mm)	L1 (mm)	A (mm)	L2 (mm)
16	10	3/8	VRV21F160	1	0.110	48	14	50	76
16	15	1/2	VRV21F200	1	0.110	48	16	50	80
16	20	3/4	VRV21F250	1	0.197	53	19	59	91
16	25	1	VRV21F320	1	0.268	58	22	68	102
16	32	1 1/4	VRV21F400	1	0.386	68	24	80	116
16	40	1 1/2	VRV21F500	1	0.555	78	24	94	126
16	50	2	VRV21F630	1	1.002	93	28	115	149
*	10	65	2 1/2	VRV21F750	1	2.900	118	33	168
	10	80	3	VRV21F900	1	3.002	140	36	168

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland

Phone +41 -(0)52-631 1111

e-mail: info.ps@georgfischer.com

Internet: <http://www.gfps.com>