



SYGEF Standard adaptor socket female Rp SDR21/PN16

Model:

- Material: PVDF
- With butt fusion spigot and parallel female thread Rp
- Avoid stresses when installing and large changes in temperature
- Connection to plastic thread only
- Do not use thread sealing pastes that are harmful to PVDF

Note:

* Please keep strictly to the GF internal installation preferences

d	SDR	Thread Type	Size	PN	FM	Code	SP	Weight
(mm)			(inch)	(bar)				(kg)
20	21	Rp	¾	16	BCF, IR	735 910 585	1	0.030
20	21	Rp	½	16	BCF, IR	735 910 586	1	0.026
25	21	Rp	¾	16	BCF, IR	735 910 587	1	0.032
32	21	Rp	1	16	BCF, IR	735 910 588	1	0.065
40	21	Rp	1 ¼	16	BCF, IR	735 910 589	1	0.092
50	21	Rp	1 ½	16	BCF, IR	735 910 590	1	0.108
*	63	21	2	16	BCF, IR	735 910 591	1	0.195

d	e	L	s	L1
(mm)	(mm)	(mm)	(mm)	(mm)
20	1.9	54	32	30
20	1.9	54	32	30
25	1.9	58	38	30
32	2.4	63	48	30
40	2.4	67	58	30
50	3.0	67	65	30
*	63	3.0	73	80

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland

Phone +41 -(0)52-631 1111

e-mail: info.ps@georgfischer.com

Internet: <http://www.gfps.com>