




SYGEF Standard
Check valve type 562
With socket fusion spigots metric

Model:

- Material: PVDF
- For horizontal or vertical installation
- Sealing at a minimum water column of 1 m
- Spring loaded, spring made of stainless steel (1.4310)
- Spring available in other materials, see spare parts
- Designed for easy installation and removal
- Vibration free even at high flow velocity
- Flow-optimized return cone, double guided
- Compact installation length, same as ball valve type 546
- Z-length, end connectors and union nuts **not** compatible with type 360

Warning: please make sure the diameter is not reduced through welding beads (Danger of turbulences)



d	DN	PN	kv-value	FKM	SP	Weight	D	L	L2	closest
(mm)	(mm)	(bar)	($\Delta p=1$ bar)	Code		(kg)	(mm)	(mm)	(mm)	inch
			(l/min)							(inch)
16	10	16	190	175 562 051	1	0.160	50	110	56	3/8
20	15	16	180	175 562 052	1	0.170	50	120	56	1/2
25	20	16	380	175 562 053	1	0.370	58	139	65	3/4
32	25	16	460	175 562 054	1	0.400	68	150	71	1
40	32	16	850	175 562 055	1	0.670	84	170	85	1 1/4
50	40	16	1080	175 562 056	1	1.030	97	190	89	1 1/2
63	50	16	1670	175 562 057	1	1.830	124	220	101	2

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland

Phone +41 -(0)52-631 1111

e-mail: info.ps@georgfischer.com

Internet: <http://www.gfps.com>