



## Pipe end peeler RSE multi

- **Rotary peeler for reliable pipe preparation prior to electrofusion**
- The adjustable basic tool is suitable for holding dimensional pipe inserts from d20 to d75 mm.
- Applicable on pipe ends and spigot ends of fittings
- Applicable for straight and coiled pipes
- Applicable for metric pipes according to EN12201 und EN1555
- Applicable on pipe material: PE100RC, PE100, PE-Xa, PP
- Operation: manual or with cordless screwdriver
- Maximum peeling length = 75mm
- Peeling blade as reversing knife with 2 cutting edges
- Scope of delivery either without or with the pipe inserts specified in the description
- Supplementary pipe inserts to be ordered separately

| d<br>(mm) | Code               | Weight<br>(kg) | Description                      | SDR | e<br>(mm) | L<br>(mm) | B<br>(mm) | H<br>(mm) |
|-----------|--------------------|----------------|----------------------------------|-----|-----------|-----------|-----------|-----------|
|           | <b>799 300 350</b> | 0.58           | Basic tool + box                 |     |           | 280       | 95        | 98        |
|           | <b>799 300 351</b> | 1.45           | Basic tool + case                |     |           | 391       | 304       | 134       |
|           | <b>799 300 352</b> | 1.88           | Basic tool+case+d32+d63          | 11  |           | 391       | 304       | 134       |
|           | <b>799 300 353</b> | 2.18           | Basic tool+case +d32+d40+d50+d63 | 11  |           | 391       | 304       | 134       |
| 20        | <b>799 300 354</b> | 0.30           | Insert RSE                       | 7   | 3.0       | 45        | 20        | 20        |
| 20        | <b>799 300 356</b> | 0.05           | Insert RSE                       | 11  | 2.0       | 45        | 20        | 20        |
| 25        | <b>799 300 355</b> | 0.10           | Insert RSE                       | 9   | 3.0       | 45        | 25        | 25        |
| 25        | <b>799 300 357</b> | 0.10           | Insert RSE                       | 11  | 2.3       | 45        | 25        | 25        |
| 32        | <b>799 300 358</b> | 0.10           | Insert RSE                       | 11  | 3.0       | 50        | 30        | 30        |
| 40        | <b>799 300 359</b> | 0.10           | Insert RSE                       | 11  | 3.7       | 50        | 40        | 40        |
| 50        | <b>799 300 360</b> | 0.20           | Insert RSE                       | 11  | 4.6       | 60        | 50        | 50        |
| 50        | <b>799 300 370</b> | 0.20           | Insert RSE                       | 17  | 3.0       | 60        | 50        | 50        |
| 63        | <b>799 300 361</b> | 0.33           | Insert RSE                       | 11  | 5.8       | 60        | 60        | 60        |
| 63        | <b>799 300 371</b> | 0.33           | Insert RSE                       | 17  | 3.8       | 60        | 60        | 60        |
| 75        | <b>799 300 362</b> | 0.47           | Insert RSE                       | 11  | 6.8       | 60        | 70        | 70        |
| 75        | <b>799 300 372</b> | 0.47           | Insert RSE                       | 17  | 4.5       | 60        | 70        | 70        |
|           | <b>799 300 347</b> | 0.01           | Blade RSE                        |     |           | 7         | 7         | 3         |
|           | <b>790 308 450</b> | 0.08           | Handle RSE                       |     |           | 60        | 50        | 50        |

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland

Phone +41 -(0)52-631 1111

e-mail: [info.ps@georgfischer.com](mailto:info.ps@georgfischer.com)

Internet: <http://www.gfps.com>