



Type 2507 Mini-Flow

Flow:

- Installs into pipe sizes: G 1/4 in, 1/4 NPT
- Operating range: 400 to 12,000 ml/m (0.1 to 3.2 U.S. gpm)
- Max Pressure rating: 5.5 bar 24 °C, 80 psi @ 75 °F
- Power source: 5 to 24V DC @ 10mA
- Compatibility: 8900, 9900, 9900-1BC, 9950

MFR #	Description	Flow Range (l/min)	Seal	Code
	1 mm insert (available through Georg Fischer DZS only)	0.1 - 2.0	FKM	198 801 731
3-2507.100-2V	2 mm insert	0.4 - 2.8	FKM	198 801 732
3-2507.100-3V	3 mm insert	0.7 - 4.2	FKM	198 801 733
3-2507.100-4V	4 mm insert	1.3 - 6.0	FKM	198 801 734
3-2507.100-6V	6 mm inlet, no insert	3.2 - 12.0	FKM	198 801 736

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland

Phone +41 -(0)52-631 1111

e-mail: info.ps@georgfischer.com

Internet: <http://www.gfps.com>