



Installation fitting type 312 ABS metric

Model:

- Saddle with threaded outlet 1 1/4" NPSM
- Top saddle for solvent cement bonding
- Material: ABS

Range of use:

- Compatible Signet flow sensors: type 2551, 2537, 515, 8510, 2536, 8512

Attention:

- sensor length depends on installation fitting

d (mm)	DN (mm)	PN (bar)	Code	SP	Weight (kg)	D (mm)	H (mm)	Sensor Type	closest inch (inch)
75	65	10	729 312 012	1	0.170	38	91	flow X1	2 1/2
90	80	10	729 312 013	1	0.176	38	91	flow X1	3
110	100	10	729 312 014	1	0.172	38	91	flow X1	4
140	125	10	729 312 016	1	0.166	38	81	flow X1	5
160	150	10	729 312 017	1	0.166	38	77	flow X1	6
200	200	10	729 312 019	1	0.152	38	71	flow X1	8
225	200	10	729 312 020	1	0.196	38	67	flow X1	8

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland

Phone +41 -(0)52-631 1111

e-mail: info.ps@georgfischer.com

Internet: <http://www.gfps.com>