



SYGEF Standard adaptor nipple male thread R SDR21/PN16

Model:

- Avoid stresses when installing and large changes in temperature
- Material: PVDF
- With butt fusion spigot and BSP tapered male thread
- Connection to plastic thread only
- Do not use thread sealing pastes that are harmful to PVDF

d	Thread Type	Size	PN	SDR	FM	Code	SP	Weight	e	L	s	L1
(mm)		(inch)	(bar)					(kg)	(mm)	(mm)	(mm)	(mm)
20	R	3/8	16	21	BCF, IR	735 910 555	1	0.024	1.9	50	32	26
20	R	1/2	16	21	BCF, IR	735 910 556	1	0.025	1.9	53	32	26
25	R	3/4	16	21	BCF, IR	735 910 557	1	0.035	1.9	55	36	26
32	R	1	16	21	BCF, IR	735 910 558	1	0.054	2.4	57	46	26
40	R	1 1/4	16	21	BCF, IR	735 910 559	1	0.076	2.4	60	55	26
50	R	1 1/2	16	21	BCF, IR	735 910 560	1	0.123	3.0	63	65	26
63	R	2	16	21	BCF, IR	735 910 561	1	0.166	3.0	69	75	27

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland

Phone +41 -(0)52-631 1111

e-mail: info.ps@georgfischer.com

Internet: <http://www.gfps.com>