





SYGEF Standard Check valve type 561
Without spring
With fixed flanges metric

Model:

- Material: PVDF
- Sealing at a minimum water column of 2 m
- Designed for easy installation and removal
- Vibration free even at high flow velocity
- Flow-optimized return cone, double guided
- For vertical installation
- Compact installation length, same as ball valve type 546
- Installation length according to EN 558-1
- Z-length, end connectors and union nuts **not** compatible with type 360
- Connecting dimension: ISO 7005 PN10, EN 1092 PN10, DIN 2501 PN10

Warning: please make sure the diameter is not reduced through welding beads (Danger of turbulences)

d (mm)	DN (mm)	Size (inch)	PN (bar)	kv-value ($\Delta p=1$ bar) (l/min)	FKM Code	SP	Weight (kg)
20	15	½	16	180	175 561 192	1	0.420
25	20	¾	16	380	175 561 193	1	0.700
32	25	1	16	460	175 561 194	1	0.860
40	32	1 ¼	16	850	175 561 195	1	1.430
50	40	1 ½	16	1080	175 561 196	1	1.940
63	50	2	16	1670	175 561 197	1	3.160

d (mm)	D (mm)	D1 (mm)	D3 (mm)	L (mm)	L2 (mm)	L3 (mm)	closest inch (inch)
20	93	65	14	120	56	130	½
25	103	75	14	140	65	150	¾
32	115	85	14	150	71	160	1
40	137	100	18	170	85	180	1 ¼
50	147	110	18	190	89	200	1 ½
63	162	125	18	220	101	230	2

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland

Phone +41 -(0)52-631 1111

e-mail: info.ps@georgfischer.com

Internet: <http://www.gfps.com>