



Adaptor socket nipple ABS metric R

Model:

- With solvent cement spigot/socket metric and taper male thread R
- Do not use thread sealing pastes that are harmful to ABS

PN (bar)	d (mm)	Thread Type	Size (inch)	d1 (mm)	Code	SP	Weight (kg)	closest inch (inch)	z (mm)	z1 (mm)	s (mm)
10	16	R	½	20	729 910 556	10	0.012	¾	42	28	32
10	20	R	¾	25	729 910 557	10	0.017	½	47	31	36
10	25	R	1	32	729 910 558	10	0.030	¾	54	35	46
10	32	R	1 ¼	40	729 910 559	10	0.046	1	60	38	55
10	40	R	1 ½	50	729 910 560	10	0.072	1 ¼	66	40	65
10	50	R	2	63	729 910 561	5	0.125	1 ½	78	47	80

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland

Phone +41 -(0)52-631 1111

e-mail: info.ps@georgfischer.com

Internet: <http://www.gfps.com>