



## Type 2540 Stainless Steel Hot Tap

### Flow:

- Installs into pipe sizes: DN40 to DN 900, 1.5 in. to 36 in.
- Operating range: 0.1 to 6 m/s, 0.3 to 20 ft/s
- Max Pressure rating: 17 bar @ 100 °C, 250 psi @ 212 °F Optional EPDM: 17 bar @ 82 °C, 250 psi @ 180 °F
- Power source: 5 to 24V DC, 1.5mA max
- Compatibility: 8900, 9900, 9900-1BC, 9950
- \*Recommended 198 820 008 (3-1500.663) Hot Tap installation tool (sold separately)

| MFR #     | Mounting           | Rotor Pin       | Code               |
|-----------|--------------------|-----------------|--------------------|
| 3-2540-3  | 1.5 in. NPT thread | Tungsten Carb.  | <b>198 840 037</b> |
| 3-2540-4  | 1.5 in. ISO thread | Tungsten Carb.  | <b>198 840 038</b> |
| 3-2540-3S | 1.5 in. NPT thread | Stainless Steel | <b>159 001 503</b> |
| 3-2540-4S | 1.5 in. ISO thread | Stainless Steel | <b>159 001 504</b> |

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland

Phone +41 -(0)52-631 1111

e-mail: [info.ps@georgfischer.com](mailto:info.ps@georgfischer.com)

Internet: <http://www.gfps.com>