



Installation fitting type 312 PVC-U metric clamp on saddle

Model:

- Saddle with threaded outlet 1 1/4" NPSM
- Top saddle for solvent cement bonding
- Seal: Lip seal EPDM

Range of use:

- Compatible Signet flow sensors: type 2551, 2537, 515, 8510, 2536, 8512
- Compatible Signet pH/ORP sensors: type 2724, 2725, 2726, 2734, 2736, 2735

Attention:

- sensor length depends on installation fitting

DN (mm)	PN	d (mm)	Code	SP	Weight (kg)	Sensor Type	H (mm)	L (mm)
65	16	75	198 150 538	1	0.780	flow X0, pH XX	99	105
80	16	90	198 150 539	1	0.835	flow X0, pH XX	105	105
100	16	110	198 150 540	1	0.885	flow X0, pH XX	114	105
150	16	160	198 150 543	1	1.375	flow X1	157	120
200	16	225	198 150 545	1	1.700	flow X1	184	120

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland

Phone +41 -(0)52-631 1111

e-mail: info.ps@georgfischer.com

Internet: <http://www.gfps.com>