



## Type 2100

### Flow:

- Installs into pipe sizes: 0.5 in, DN15 Hose size: DN8, 1/4 in, DN10, 3/8 in, DN15, 0.5 in
- Operating range: 0.38 to 38 lpm, 0.8 to 10 gpm
- Max Pressure rating: 16 bar @ 20 °C, 232 psi @ 68 °F
- Power source: 5 to 24V DC, 1.5mA max
- Compatibility: 8900, 9900, 9900-1BC, 9950
- \*End connector kits must be ordered separately. See accessories
- \*-H version can be used with flare fitting. Flow range: 3 - 27 lpm

	MFR #	Description	Flow Range	Code
*	3-2100-1L	FKM o-ring	0.38-3.8 lpm (0.10-1 gpm)	<b>159 000 001</b>
*	3-2100-2L	EPDM o-ring	0.38-3.8 lpm (0.10-1 gpm)	<b>159 000 003</b>
*	3-2100-1H	FKM o-ring	3.0-38.0 lpm (0.8-10 gpm)	<b>159 000 002</b>
*	3-2100-2H	EPDM o-ring	3.0-38.0 lpm (0.8-10 gpm)	<b>159 000 004</b>

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland

Phone +41 -(0)52-631 1111

e-mail: [info.ps@georgfischer.com](mailto:info.ps@georgfischer.com)

Internet: <http://www.gfps.com>