

## HYDRAULIC OIL



Premium grade hydraulic oil

High viscosity index

Supplied in a choice of 1, 5 or 25 litre containers

- Effective and reliable lubricant
- Foaming resistance
- Provides optimum performance in all high pressure applications
- Specially formulated for use with all Hi-Force hydraulic tools

Model number	Contents (litres)
HFO15-1	1
HFO15-5	5
HFO15-25	25
HFO46-1	1
HFO46-5	5
HFO46-25	25

### OIL TYPE RECOMMENDATION

Product	Oil Type	HFO15	HFO46
ACP	✓	•	
AHP/AHP-CR/AHP2/ AHP2-CR/ATDP	•	✓	
AHP-BTU	•	✓	
AHP11	•	✓	
BC	•	✓	
BPP	•	✓	
CH	•	✓	
Controlled Manifolds	✓	✓	
Couplers & Fittings	✓	✓	
CT	✓	•	
Digital Gauge	✓	✓	
DNS	•	✓	
Gauge/Blocks	✓	✓	
HAP	-	✓	
HAS	•	✓	
HCC	•	✓	
HCH	•	✓	
HDA	•	✓	
HEP1	•	✓	
HEP103	•	✓	
HEP2/HEP3/HEP4/HEP5	-	✓	
HFA	•	✓	
HFG	•	✓	
HFL	•	✓	
HFS-H	•	✓	
HFV42/HFV66	✓	✓	
HGG	•	✓	

Product	Oil Type	HFO15	HFO46
HHA	•	✓	
HHP	•	✓	
HHR	•	✓	
HHS	•	✓	
HKP	✓	•	
HLS	•	✓	
HMJ	•	✓	
HMNS	✓	•	
Hoses	✓	✓	
HP(All)	✓	•	
HP-FP	✓	•	
HPC	•	✓	
HPF	•	✓	
HPP	-	✓	
HPR/HBR	✓	•	
HPS	•	✓	
HPT	✓	✓	
HPX	✓	•	
HPX-BTU	✓	✓	
HPV152	✓	✓	
HRA	•	✓	
HSG	•	✓	
HSP	-	✓	
HSS	•	✓	
HSWC	✓	•	
HTN	•	✓	
HTWP	-	✓	
HTWR1	•	✓	

Product	Oil Type	HFO15	HFO46
HVL	•	✓	
HWRC	•	✓	
JAH	✓	•	
JAS	✓	•	
JCS/JCH	✓	✓	
JS	✓	•	
Manifolds	✓	✓	
MHX	✓	•	
NS	•	✓	
PB	✓	•	
PKC	✓	•	
PKS	✓	•	
PMV2	•	✓	
PMV3/PMV3L	•	✓	
PMV4/PMV4L	•	✓	
RMV3/RMV3L	•	✓	
RMV4/RMV4L	•	✓	
SBT	•	✓	
SC	✓	•	
SCP	✓	•	
SJS	✓	•	
SLF/SLV	-	✓	
STS	•	✓	
STU	•	✓	
Toughlift	•	✓	
TPA	-	✓	
TPE	-	✓	
XHR1	•	✓	

Note: ✓ Recommended and factory fitted grade  
• Acceptable alternative  
- Not recommended