



PROGEF Standard Tee 90° metric Rp (PN10)

Model:

- Material: PP-H
- Line, with fusion socket metric
- Branch, with BSP parallel female thread Rp, reinforced
- Reinforcing ring stainless (A2)
- Connection to plastic or metal threads
- Do not use thread sealing pastes that are harmful to PP
- Install with low mechanical stress and avoid large cyclic temperature changes

d (mm)	Thread Type	Size (inch)	PN (bar)	Code	SP	GP	Weight (kg)	D (mm)	D1 (mm)	L (mm)	z1 (mm)	z2 (mm)
20	Rp	½	10	727 200 206	10	90	0.030	31	30	28	14	14
20	Rp	¾	10	727 200 207	10	50	0.042	36	35	32	16	16
20	Rp	1	10	727 200 208	10	30	0.071	44	45	38	20	20
20	Rp	1 ¼	10	727 200 209	10	30	0.107	54	55	44	24	24

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland

Phone +41 -(0)52-631 1111

e-mail: info.ps@georgfischer.com

Internet: <http://www.gfps.com>