



Saddle with female thread Rp PVC-U

d (mm)	Rp (inch)	PN (bar)	Code	SP	Weight (kg)	P (mm)	E (mm)	L (mm)	Z (mm)
32	1/4	10	DV0DEF32Z	15	0.010	11	24.2	12.9	28.9
40	3/8	10	DV0DEF40A	15	0.009	11	24.2	14.0	32.0
50	1/4	10	DV0DEF50Z	15	0.011	11	24.2	12.9	37.9
50	3/8	10	DV0DEF50A	15	0.010	11	24.2	14.0	37.0
50	1/2	10	DV0DEF50B	15	0.015	14	30.0	15.0	42.0
50	3/4	10	DV0DEF50C	10	0.023	19	36.0	16.3	43.0
63	3/8	10	DV0DEF63A	15	0.009	11	24.2	14.0	43.5
63	1/2	10	DV0DEF63B	10	0.015	14	30.0	15.0	48.0
63	3/4	10	DV0DEF63C	10	0.020	19	36.0	16.3	49.0
75	3/8	10	DV0DEF75A	15	0.009	11	24.2	14.0	49.5
75	3/4	10	DV0DEF75C	10	0.022	19	36.0	16.3	55.0
75	1	10	DV0DEF75D	10	0.039	24	45.0	19.1	56.0
90	1/2	10	DV0DEF90B	15	0.015	14	30.0	15.0	62.0
90	1	10	DV0DEF90D	10	0.036	24	45.0	19.1	64.0
90	1 1/2	10	DV0DEF90F	24	0.090	38	64.0	21.4	66.0
110	1/2	10	DV0DEF91B	15	0.015	14	30.0	15.0	72.0

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland

Phone +41 -(0)52-631 1111

e-mail: info.ps@georgfischer.com

Internet: <http://www.gfps.com>