






PROGEF Standard 3-Way ball valve type 543
Horizontal/L-port
With butt fusion spigots IR-Plus SDR11 metric

Model:

- Material: PP-H
- For easy installation and removal (valve end and union nut are compatible with type 546)
- Ball seals PTFE
- Pneumatic or electric actuator available separately
- Angle of operation 360° without turn limiter
- Turn limiter 90° enclosed, in different positions usable as a clip-on ring
- Integrated stainless steel mounting inserts
- Delivery status A-C opened, see flow scheme



d	DN	Size	PN	kv-value	EPDM	Weight	FKM	Weight
(mm)	(mm)	(inch)	(bar)	($\Delta p=1$ bar)	Code	(kg)	Code	(kg)
				(l/min)				
20	15	½	10	75	167 543 062	0.171	167 543 072	0.171
25	20	¾	10	150	167 543 063	0.247	167 543 073	0.247
32	25	1	10	280	167 543 064	0.377	167 543 074	0.377
40	32	1 ¼	10	480	167 543 065	0.629	167 543 075	0.629
50	40	1 ½	10	620	167 543 066	0.989	167 543 076	0.953
63	50	2	10	1230	167 543 067	1.928	167 543 077	1.855

d	D	H	H1	H2	L	L1	L2	L3	L4	L5	L6	M	e	closest
(mm)	(mm)	(mm)	(mm)	(mm)	(mm)	(mm)	(mm)	(mm)	(mm)	(mm)	(mm)	(mm)	(mm)	inch
														(inch)
20	50	57	28	8	146	77	72	36	25	32	45	6	1.9	½
25	58	67	32	8	163	97	85	43	25	39	58	6	2.3	¾
32	68	73	36	8	178	97	98	49	25	39	58	6	2.9	1
40	84	90	45	9	204	128	118	59	45	54	74	8	3.7	1 ¼
50	97	97	51	9	237	128	135	68	45	54	74	8	4.6	1 ½
63	124	116	65	9	296	152	176	88	45	66	87	8	5.8	2

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland

Phone +41 -(0)52-631 1111

e-mail: info.ps@georgfischer.com

Internet: <http://www.gfps.com>