






Solenoid valve type 160 PVC-U
Straight through valve 2/2 ways

Model:

- Material: PVC-U
- With solvent cement socket metric
- With manual override
- Electrical connection: cable plug
- Protection class IP 65
- Circuit function A: FC, closed in rest position
- Circuit function B: FO, opened in rest position



d (mm)	DN (mm)	Size (inch)	PN (bar)	Voltage	PN (bar)	kv-value (Δp=1 bar) (L/min)	Function
16	10	¾	3.0	230V 50Hz ± 10%	0.0 - 3.0	33	A
20	10	½	3.0	230V 50Hz ± 10%	0.0 - 3.0	33	A
20	15	½	1.0	230V 50Hz ± 10%	0.0 - 1.0	75	A
25	15	½	1.0	230V 50Hz ± 10%	0.0 - 1.0	75	A
25	20	¾	0.5	230V 50Hz ± 10%	0.0 - 0.5	100	A
16	10	¾	2.0	230V 50Hz ± 10%	0.0 - 2.0	33	B
20	10	½	1.0	230V 50Hz ± 10%	0.0 - 2.0	33	B
20	15	½	1.0	230V 50Hz ± 10%	0.0 - 1.0	75	B
25	15	¾	1.0	230V 50Hz ± 10%	0.0 - 1.0	75	B
25	20	¾	0.5	230V 50Hz ± 10%	0.0 - 0.5	100	B
16	10	¾	3.0	24V AC/DC	0.0 - 3.0	33	A
20	10	½	3.0	24V AC/DC	0.0 - 3.0	33	A
20	15	½	1.0	24V AC/DC	0.0 - 1.0	75	A
25	15	¾	1.0	24V AC/DC	0.0 - 1.0	75	A
25	20	¾	0.5	24V AC/DC	0.0 - 0.5	100	A
16	10	¾	2.0	24V AC/DC	0.0 - 2.0	33	B
20	10	½	2.0	24V AC/DC	0.0 - 2.0	33	B
25	20	¾	0.5	24V AC/DC	0.0 - 0.5	100	B

d (mm)	EPDM Code	FKM Code	L (mm)	L1 (mm)	L2 (mm)
16	199 160 010	199 160 005	130	17	14
20	199 160 011	199 160 006	134	19	16
20	199 160 012	199 160 007	136	19	16
25	199 160 013	199 160 008	142	22	19
25	199 160 014	199 160 009	144	22	19
16	199 160 025	199 160 020	130	17	14
20	199 160 026	199 160 021	134	19	16
20	199 160 027	199 160 022	136	19	16
25	199 160 028	199 160 023	142	19	19
25	199 160 029	199 160 024	144	22	19
16	199 160 370	199 160 365	130	17	14
20	199 160 371	199 160 366	134	19	16
20	199 160 372	199 160 367	136	19	16
25	199 160 373		142	22	19
25	199 160 374	199 160 369	144	22	19
16	199 160 385	199 160 380	130	17	14
20	199 160 386	199 160 381	134	19	16
25	199 160 389		144	22	19

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Data sheet

valid from: 6/15/21



Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland

Phone +41 -(0)52-631 1111

e-mail: info.ps@georgfischer.com

Internet: <http://www.gfps.com>