


PROGEF Standard Diaphragm valve type 605 With butt fusion spigot metric

Model:

- Material: PP-H
- Compact full plastic design without screws
- High flow rate
- Actuator housing with thread for easy maintenance
- Quick opening & closing times
- For easy installation and removal
- Market standard installation length

Option:

- Individual configuration of the valve

* O-Ring material: FKM

d (mm)	DN (mm)	Size (inch)	PN (bar)	kv-value ($\Delta p=1$ bar) (l/min)	Actuator
-----------	------------	----------------	-------------	--	----------

20	15	½	6	125	FC
20	15	½	6	125	FO
20	15	½	6	125	DA

d (mm)	EPDM Code	FKM Code	PTFE/ EPDM* Code	Weight (kg)
-----------	--------------	-------------	------------------------	----------------

20	167 605 112	167 605 162	167 605 132	0.31
20	167 605 114	167 605 164	167 605 134	0.28
20	167 605 115	167 605 165	167 605 135	0.26

d (mm)	D (mm)	D1_G (inch)	H (mm)	H1 (mm)	H2 (mm)	H3 (mm)	H4 (mm)	H7 (mm)	L (mm)	L2 (mm)	e (mm)	M	z (mm)	Lift = Hx (mm)
-----------	-----------	----------------	-----------	------------	------------	------------	------------	------------	-----------	------------	-----------	---	-----------	-------------------

20	65	¼	89	14	12	46	30	42	124	25	1.9	M6	100	6
20	65	¼	89	14	12	46	30	42	124	25	1.9	M6	100	6
20	65	¼	89	14	12	46	30	42	124	25	1.9	M6	100	6

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland

Phone +41 -(0)52-631 1111

e-mail: info.ps@georgfischer.com

Internet: <http://www.gfps.com>