



Reducing bush PVC-U R Rp

Model:

- With taper male thread R and parallel female thread Rp
- Install with low mechanical stress and avoid large cyclic temperature changes
- Do not use thread sealing pastes that are harmful to PVC-U

Thread Type	Thread Type 2	Size 2 (inch)	Size (inch)	PN (bar)	Code	SP	Weight (kg)	z (mm)	L (mm)	s (mm)
R	Rp	3/8	1/2	10	721 910 834	10	0.014	25	36	27
R	Rp	1/2	3/4	10	721 910 837	10	0.021	25	39	32
R	Rp	1/2	1	10	721 910 842	10	0.029	31	45	32
R	Rp	3/4	1	10	721 910 841	10	0.031	29	45	36
R	Rp	1	1 1/4	10	721 910 846	10	0.050	32	50	46
R	Rp	1 1/4	1 1/2	10	721 910 852	10	0.065	35	55	55
R	Rp	1 1/2	2	10	721 910 858	5	0.127	45	65	65

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland

Phone +41 -(0)52-631 1111

e-mail: info.ps@georgfischer.com

Internet: <http://www.gfps.com>