



Data sheet

valid from: 11/5/20



Transition union module - flat sealed

Supplied with sealing

** on request

low-lead brass, dezincification resistant

	G	d	Code	SP	Weight	z
	(inch)	(mm)			(kg)	(mm)
**	½	16 - 20	762 101 088	2	0.080	41
	¾	16 - 20	762 101 056	2	0.085	35
	¾	25 - 32	762 101 095	2	0.170	48
	1	25 - 32	762 101 096	2	0.233	55
	1 ¼	25 - 32	762 101 097	2	0.266	48
	1 ½	25 - 32	762 101 098	2	0.339	50
*,**	½	16 - 20	762 101 276	2	0.070	41
*	¾	16 - 20	762 101 273	5	0.064	35
*	¾	25 - 32	762 101 281	2	0.155	48
*	1	25 - 32	762 101 282	2	0.179	55
*	1 ¼	25 - 32	762 101 283	2	0.251	48
*	1 ½	25 - 32	762 101 284	2	0.357	50

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland

Phone +41 -(0)52-631 1111

e-mail: info.ps@georgfischer.com

Internet: <http://www.gfps.com>