

Data sheet

valid from: 7/1/21



Type 2250 For Level and Depth Control 1/2 inch union connector

Temperature/Pressure:

- Cable Length: 10 m (32.8 ft)
- Operating Temperature:** 15° to 85°C (5° to 185°F)
- Operating Pressures:** -XU Ultra Low: 0 to 0.7 bar (0 to 10 psi) -XL Low: 0 to 3.4 bar (0 to 50 psi)
- Compatibility: 8900, 9900 and 9950

MFR #	Output	Maximum Operation	Code
3-2250-11U	Digital (S ³ L)	0.7 bar (10 psi); 7.03 m (23 ft)	159 001 242
3-2250-11L	Digital (S ³ L)	3.4 bar (50 psi); 35.15 m (115 ft)	159 001 241
3-2250-21U	4-20 mA	0.7 bar (10 psi); 7.03 m (23 ft)	159 001 248
3-2250-21L	4-20 mA	3.4 bar (50 psi); 35.15 m (115 ft)	159 001 247
3-2250-11U-1	Digital (S ³ L)	0.7 bar (10 psi); 7.03 m (23 ft)	159 001 478
3-2250-11L-1	Digital (S ³ L)	3.4 bar (50 psi); 35.15 m (115 ft)	159 001 479
3-2250-21U-1	4-20 mA	0.7 bar (10 psi); 7.03 m (23 ft)	159 001 482
3-2250-21L-1	4-20 mA	3.4 bar (50 psi); 35.15 m (115 ft)	159 001 483

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland

Phone +41 -(0)52-631 1111

e-mail: info.ps@georgfischer.com

Internet: <http://www.gfps.com>