



Type 525 Metalex
(use with Metalex Weld-On Mini-Tap, Socket Weld Mini-Tap)

Flow:

- Installs into pipe sizes: 0.5 to 12 in, DN15 to DN300
- Operating range: 1.6 to 20 ft/s, 0.5 to 6 m/s
- Max Pressure rating: Socket weld or weld on fittings 103 bar, 1500 psi (@ safety factor 1.5)
- Power source: Self powered
- Compatibility: 8150, 8900, 9900, 9900-1BC, 9950

MFR #	Pin	Pipe Size (inch)	DN-DN (mm)	Code
P525-1	Tungsten Carbide	0.5 - 1	15 - 25	198 801 494
P525-2	Tungsten Carbide	1.25 - 12	32 - 300	198 801 495
P525-1S	316 Stainless Steel	0.5 - 1	15 - 25	159 000 963
P525-2S	316 Stainless Steel	1.25 - 12	32 - 300	159 000 964

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland

Phone +41 -(0)52-631 1111

e-mail: info.ps@georgfischer.com

Internet: <http://www.gfps.com>