




## Ball valve type 546 PP / PB-Spigots

Applicable for compressed air till 10 bar  
 No approval for potable water installations  
 Working temperature max. +70°C  
 \* on request



	d (mm)	DN (mm)	PN (bar)	EPDM Code	SP	Weight (kg)	L1 (mm)	L2 (mm)	z (mm)
*	20	15	10	<b>760 000 343</b>	1	0.141	95	190	33
*	25	20	10	<b>760 000 344</b>	1	0.203	108	208	38
*	32	25	10	<b>760 000 345</b>	1	0.298	118	218	39
*	40	32	10	<b>760 000 346</b>	1	0.512	137	250	47
*	50	40	10	<b>760 000 347</b>	1	0.715	147	263	49
*	63	50	10	<b>760 000 348</b>	1	1.293	168	288	46

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland

Phone +41 -(0)52-631 1111

e-mail: [info.ps@georgfischer.com](mailto:info.ps@georgfischer.com)

Internet: <http://www.gfps.com>