

UNI-Grip S coupling stainless steel 1.4571
Tensile-resistant connection of metal and metal
PN 2,5 Solid bolt

Model:

- Housing, Bars and Strip insert (option): Stainless Steel W5 (1.4571) Quality

Temperature/Pressure:

- Operating temperature EPDM: -30°C to 125°C
- Operating temperature NBR: -20°C to 80°C

Option:

- Sealing type Viton (FKM) on request

Attention:



- The difference between the different pipe outside diameters OD1<OD2 is 1% or max. 3 mm.

OD nominal (mm)	EPDM Code	NBR Code	Weight (kg)
288 - 301	779 764 332	779 762 332	6.8
301 - 314	779 764 333	779 762 333	7.0
315 - 328	779 764 334	779 762 334	7.2
327 - 340	779 764 335	779 762 335	7.4
340 - 353	779 764 336	779 762 336	7.5
350 - 363	779 764 337	779 762 337	7.7
361 - 374	779 764 338	779 762 338	7.8
374 - 387	779 764 339	779 762 339	9.5
387 - 400	779 764 340	779 762 340	9.7
400 - 413	779 764 341	779 762 341	9.9
412 - 425	779 764 342	779 762 342	10.1
422 - 435	779 764 343	779 762 343	10.3
438 - 451	779 764 344	779 762 344	10.5
451 - 464	779 764 345	779 762 345	10.7
460 - 473	779 764 346	779 762 346	10.9
476 - 489	779 764 347	779 762 347	11.1
488 - 501	779 764 348	779 762 348	11.3
503 - 516	779 764 349	779 762 349	11.6
520 - 533	779 764 350	779 762 350	16.9
531 - 544	779 764 351	779 762 351	17.2
546 - 559	779 764 352	779 762 352	17.6
557 - 570	779 764 353	779 762 353	17.9
571 - 584	779 764 354	779 762 354	18.2
600 - 613	779 764 355	779 762 355	18.9
610 - 623	779 764 356	779 762 356	19.2
628 - 641	779 764 357	779 762 357	19.6
648 - 661	779 764 358	779 762 358	20.1
676 - 689	779 764 359	779 762 359	20.8
688 - 701	779 764 360	779 762 360	21.1
700 - 713	779 764 361	779 762 361	21.4
717 - 730	779 764 362	779 762 362	21.9
732 - 745	779 764 363	779 762 363	22.2

OD nominal (mm)	M	PN	WP	C max.	OD min	OD max.	OD1 < OD2	d	B	H
(mm)	(bar)	(bar)	(mm)	(mm)	(mm)	(mm)	(mm)	(mm)	(mm)	(mm)
288 - 301	M16	2.5	6	40	288	301	3	339	138	365
301 - 314	M16	2.5	6	40	301	314	3	352	138	378
315 - 328	M16	2.5	6	40	315	328	3	366	138	392
327 - 340	M16	2.5	6	40	327	340	3	378	138	404
340 - 353	M16	2.5	6	40	340	353	3	391	138	417
350 - 363	M16	2.5	6	40	350	363	3	401	138	427
361 - 374	M16	2.5	6	40	361	374	3	412	138	438
374 - 387	M16	2.5	6	40	374	387	3	425	138	451

Data sheet

valid from: 7/21/21




OD nominal (mm)	M	PN (bar)	WP (bar)	C max. (mm)	OD min (mm)	OD max. (mm)	OD1 < OD2 (mm)	d (mm)	B (mm)	H (mm)
387 - 400	M16	2.5	6	40	387	400	3	438	138	464
400 - 413	M16	2.5	6	40	400	413	3	451	138	477
412 - 425	M16	2.5	6	40	412	425	3	463	138	489
422 - 435	M16	2.5	6	40	422	435	3	473	138	499
438 - 451	M16	2.5	6	40	438	451	3	489	138	515
451 - 464	M16	2.5	6	40	451	464	3	502	138	528
460 - 473	M16	2.5	6	40	460	473	3	511	138	537
476 - 489	M16	2.5	6	40	476	489	3	527	138	553
488 - 501	M16	2.5	6	40	488	501	3	539	138	565
503 - 516	M16	2.5	6	40	503	516	3	554	138	580
520 - 533	M16	2.5	6	40	520	533	3	575	140	603
531 - 544	M16	2.5	6	40	531	544	3	586	140	614
546 - 559	M16	2.5	6	40	546	559	3	601	140	629
557 - 570	M16	2.5	6	40	557	570	3	612	140	640
571 - 584	M16	2.5	6	40	571	584	3	626	140	654
600 - 613	M16	2.5	6	40	600	613	3	655	140	683
610 - 623	M16	2.5	6	40	610	623	3	665	140	693
628 - 641	M16	2.5	6	40	628	641	3	683	140	711
648 - 661	M16	2.5	6	40	648	661	3	703	140	731
676 - 689	M16	2.5	6	40	676	689	3	731	140	759
688 - 701	M16	2.5	6	40	688	701	3	743	140	771
700 - 713	M16	2.5	6	40	700	713	3	755	140	783
717 - 730	M16	2.5	6	40	717	730	3	772	140	800
732 - 745	M16	2.5	6	40	732	745	3	787	140	815


OD nominal (mm)	Torque (N/m)
288 - 301	160
301 - 314	160
315 - 328	160
327 - 340	160
340 - 353	160
350 - 363	160
361 - 374	160
374 - 387	160
387 - 400	160
400 - 413	160
412 - 425	160
422 - 435	160
438 - 451	160
451 - 464	160
460 - 473	160
476 - 489	160
488 - 501	160
503 - 516	160
520 - 533	160
531 - 544	160
546 - 559	160
557 - 570	160
571 - 584	160
600 - 613	160
610 - 623	160
628 - 641	160
648 - 661	160
676 - 689	160

Data sheet

valid from: 7/21/21



OD nominal (mm) (mm)	Torque (N/m)
688 - 701	160
700 - 713	160
717 - 730	160
732 - 745	160



The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland

Phone +41 -(0)52-631 1111

e-mail: info.ps@georgfischer.com

Internet: <http://www.gfps.com>