



## SYGEF Plus Installation fitting with sanitary adaptor SDR 21 / PN 16

### Model:


- without chamfer for complete evacuation even in horizontal installation
- Material: PVDF-HP
- d [mm] = main line
- D [mm] = connector line

### Range of use:

- for pressure gauges
- for sampling valves
- for sanitary adaptor PVDF connection

### Note:

\* machined T



|   | d<br>(mm) | D<br>(mm) | FM      | PN | SDR | Code               | SP | Weight<br>(kg) | L<br>(mm) | D2<br>(mm) | D1<br>(mm) | Z<br>(mm) |
|---|-----------|-----------|---------|----|-----|--------------------|----|----------------|-----------|------------|------------|-----------|
| * | 20        | 20        | BCF, IR | 16 | 21  | <b>735 318 101</b> | 1  | 0.100          | 110       | 34.1       | 50.5       | 32.7      |
| * | 25        | 25        | BCF, IR | 16 | 21  | <b>735 318 202</b> | 1  | 0.097          | 110       | 34.1       | 50.5       | 35.2      |
| * | 32        | 32        | BCF, IR | 16 | 21  | <b>735 318 303</b> | 1  | 0.138          | 124       | 34.1       | 50.5       | 38.7      |
| * | 40        | 25        | BCF, IR | 16 | 21  | <b>735 318 204</b> | 1  | 0.100          | 124       | 19.9       | 50.5       | 42.7      |
| * | 40        | 32        | BCF, IR | 16 | 21  | <b>735 318 304</b> | 1  | 0.100          | 124       | 25.6       | 50.5       | 42.7      |
| * | 50        | 25        | BCF, IR | 16 | 21  | <b>735 318 205</b> | 1  | 0.100          | 124       | 19.9       | 50.5       | 47.7      |
| * | 50        | 32        | BCF, IR | 16 | 21  | <b>735 318 305</b> | 1  | 0.100          | 124       | 25.6       | 50.5       | 47.7      |
| * | 50        | 50        | BCF, IR | 16 | 21  | <b>735 318 505</b> | 1  | 0.100          | 124       | 42.2       | 64.0       | 47.7      |
|   | 63        | 25        | BCF, IR | 16 | 21  | <b>735 318 206</b> | 1  | 0.258          | 120       | 19.9       | 50.5       | 54.2      |
|   | 63        | 32        | BCF, IR | 16 | 21  | <b>735 318 306</b> | 1  | 0.269          | 120       | 25.6       | 50.5       | 54.2      |
| * | 63        | 50        | BCF, IR | 16 | 21  | <b>735 318 506</b> | 1  | 0.100          | 120       | 42.2       | 64.0       | 54.2      |
| * | 63        | 63        | BCF, IR | 16 | 21  | <b>735 318 606</b> | 1  | 0.100          | 138       | 55.1       | 77.5       | 54.2      |
|   | 75        | 25        | BCF, IR | 16 | 21  | <b>735 318 207</b> | 1  | 0.352          | 130       | 19.9       | 50.5       | 60.2      |
|   | 75        | 32        | BCF, IR | 16 | 21  | <b>735 318 307</b> | 1  | 0.357          | 130       | 25.6       | 50.5       | 60.2      |
|   | 75        | 50        | BCF, IR | 16 | 21  | <b>735 318 507</b> | 1  | 0.402          | 130       | 42.2       | 64.0       | 60.2      |
| * | 75        | 63        | BCF, IR | 16 | 21  | <b>735 318 607</b> | 1  | 0.619          | 130       | 55.1       | 77.5       | 60.2      |
|   | 90        | 25        | BCF, IR | 16 | 21  | <b>735 318 208</b> | 1  | 0.449          | 130       | 19.9       | 50.5       | 67.7      |
|   | 90        | 32        | BCF, IR | 16 | 21  | <b>735 318 308</b> | 1  | 0.454          | 130       | 25.6       | 50.5       | 67.7      |
|   | 90        | 50        | BCF, IR | 16 | 21  | <b>735 318 508</b> | 1  | 0.496          | 130       | 42.2       | 64.0       | 67.7      |
|   | 90        | 63        | BCF, IR | 16 | 21  | <b>735 318 608</b> | 1  | 0.658          | 138       | 55.1       | 77.5       | 67.7      |
|   | 110       | 25        | BCF, IR | 16 | 21  | <b>735 318 209</b> | 1  | 0.614          | 130       | 19.9       | 50.5       | 77.7      |
|   | 110       | 32        | BCF, IR | 16 | 21  | <b>735 318 309</b> | 1  | 0.619          | 130       | 25.6       | 50.5       | 77.7      |
|   | 110       | 50        | BCF, IR | 16 | 21  | <b>735 318 509</b> | 1  | 0.662          | 130       | 42.2       | 64.0       | 77.7      |
|   | 110       | 63        | BCF, IR | 16 | 21  | <b>735 318 609</b> | 1  | 0.686          | 180       | 55.1       | 77.5       | 77.7      |

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland

Phone +41 -(0)52-631 1111

e-mail: [info.ps@georgfischer.com](mailto:info.ps@georgfischer.com)

Internet: <http://www.gfps.com>